

IN THE CLAIMS

Please amend the status of the claims to that as indicated below:

Claims 1-35 (canceled)

36. (currently amended) A detachable connection of two elements, comprising:

~~a bolt arranged between the two elements detachably connected;~~

a bolt;

two elements detachably connected to one another via said bolt;

a tensioning body having an azimuthally extending slot through which said bolt is penetratable for fixing said bolt at one end to one element of the two elements, said tensioning body being rotatable relative to said one element about an axis extending substantially perpendicular to said bolt with said tensioning body being ~~fixed~~ connected in any rotational position relative to said bolt; and,

means for fastening said bolt to said tensioning body, said means for fastening being rotatable about an axis that is distanced from ~~the~~ a substantially central axis of said tensioning body and substantially parallel thereto, said means for fastening including a retaining head detachably attached to said bolt and being rotatable relative to said tensioning body.

37. (currently amended) The detachable connection of two elements according to Claim 36, wherein said bolt has a second end opposite said one end, or ~~said~~ a first end, with ~~said~~ a second end of said bolt being fastened ~~a~~ ~~second~~ to one element of said two elements.

38. (currently amended) The detachable connection of two elements according to Claim 36, wherein said bolt has a second end opposite said one end, or ~~said~~ a first end, with said bolt being fixed at its ~~said~~ second end via an additional tensioning body to a second element of said two elements, said additional tensioning body being rotatable relative to said second element about an axis extending substantially perpendicular to said bolt, and further comprising additional means for fastening said additional tensioning body to said bolt, said additional means for fastening being rotatable about an axis distanced from an axis of said additional tensioning body and substantially parallel thereto, said additional tensioning body being ~~fixed~~ connected in any rotational position relative to said bolt.

39. (previously presented) The detachable connection of two elements according to Claim 36, wherein said bolt penetrates at least one of said two elements.

40. (currently amended) The detachable connection of two elements according to Claim 36, wherein said tensioning

body is accommodated ~~in of said~~ in said one element of said two elements ~~fixing~~ connecting said tensioning body.

41. (previously presented) The detachable connection of two elements according to Claim 36, wherein said retaining head is detachably connected to said tensioning body.

Claims 42-47 (canceled)

48. (previously presented) The detachable connection of two elements according to Claim 36, wherein said tensioning body is of a substantially cylindrical shape.

49. (previously presented) The detachable connection of two elements according to Claim 36, wherein said retaining head is of a substantially cylindrical shape.

50. (previously presented) The detachable connection of two elements according to Claim 36, wherein said one element of said two elements is open on an axial end face.

51. (previously presented) The detachable connection of two elements according to Claim 36, wherein a cavity of said tensioning body is open on an axial end face.

52. (previously presented) The detachable connection of two elements according to Claim 36, wherein said one element of said two elements is closed on an axial end face.

Claim 53 (canceled)